

WO 2004/021472
SC/WY 020564WO
August 26, 2002

101523543
Rec'd PCT/PTC 31 JAN 2005
PCT/IB2002/083473

Battery holder

FIELD OF THE INVENTION

The invention relates to a battery holder for an electronic device. The invention relates equally to an electronic device and to a cover for an electronic device comprising such a battery holder.

BACKGROUND OF THE INVENTION

The power source required by electronic devices for their operation may be given in particular in the case of mobile electronic devices by a battery. Such a battery may have to be changed occasionally.

It is known to place the battery into a spacing provided in the electronic device and to close the spacing with a cover.

In patent US 6,120,932, for example, it is proposed to employ a battery tray into which a battery cell is inserted. The tray is then fixed in a radio housing. A back cover finally slides over the radio housing to encapsulate the battery cells.

Patent US 5,667,906 presents a storage battery comprising a base housing and a cover housing, which form a receiving space for receiving an electric circuit board and a battery. The storage battery can then be inserted with the base housing as a leading side into a mounting

CONFIRMATION COPY

room provided in a mobile phone to be electrically connected therewith.

It might be considered a disadvantage by some users that the cover covering a battery which was inserted into a spacing provided in an electronic device is often very light, whereby its handling resembles to the handling of a toy. Moreover, such a cover is usually not particularly robust.

In an equally known alternative, the battery and the cover are realized as a permanently fixed unit. This approach has the disadvantage, however, that whenever the battery has to be exchanged, the customer has to buy a new entity comprising the battery and the cover, which is rather expensive.

SUMMARY OF THE INVENTION

It is an object of the invention to provide a improved possibility for exchanging a battery module of an electronic device.

This object is reached according to the invention with a battery holder for an electronic device comprising an outer surface, means for receiving at least one exchangeable battery at a side opposite to this outer surface and means for connecting the battery holder releasably to an electronic device. The latter means enable a connection of the battery holder to the electronic device in a way that electrical contact elements of at least one battery received by the battery holder come into contact with electrical contact elements

of the electronic device and that the outer surface of the battery holder forms part of the outer surface of the electronic device.

The object of the invention is equally reached with a cover for an electronic device, which cover comprises the proposed battery holder. The battery holder is connected to the cover by the proposed means for releasably connecting the battery holder to an electronic device. It is to be noted that the electrical connection between a battery received by the battery holder and the electronic device is only achieved when the cover has been connected to the electronic device.

Further, the object of the invention is reached with an electronic device comprising the proposed battery holder, wherein the battery holder is connected to the electronic device by the proposed means for releasably connecting the battery holder to an electronic device. The battery holder is preferably connected more specifically to a cover of the electronic device.

The invention proceeds from the idea that a part of the housing of an electronic device might be realized as a battery holder, to which a battery module may be connected in a releasable way.

The combination of battery module and battery holder can be connected to and removed from the electronic device comfortably as one integrated package. Still, the user of the electronic device can exchange the battery by itself without the battery holder when the battery life time has been reached. Thus, the user only has to buy a new

battery, not a complete battery holder or cover comprising a battery module, whenever the battery module has to be exchanged.

It is further an advantage of the invention that the integration of battery module and battery holder makes the removable part more robust compared to a cover by itself. At the same time, the battery holder protects the battery from mechanical stresses, especially when the mechanical construction of the battery module itself is thin and weak. Nowadays, batteries usually do not comprise rigid plastic parts at both ends any more. Instead, they are often only covered with an adhesive tape.

It is equally an advantage of the invention that it enables to save costs in the production, since the battery module is assembled by the user. The invention also facilitates logistics and thus allows an increase in battery production. Moreover, a standard battery can be used for the battery module, while design based product variants can be made by varying the surface of the battery holder.

Preferred embodiments of the invention become apparent from the dependent claims.

The at least one battery can be combined with the battery module in any suitable manner.

Preferably, a battery is connected to a battery holder by sliding the battery along guiding elements provided on the battery holder. The dimensions of the receiving space

defined by the guiding elements should be such that it is suitably tight to hold the battery.

The battery holder may comprise in addition locking means, which may fix the battery to the battery holder and/or adjust the size of the receiving space of the battery holder to a variable battery size.

The battery holder can also be connected to the electronic device in any suitable manner.

Preferably, this connection is realized as a snapping connection. In order to ensure a secure connection, a button interacting with the snapping connection either on the side of the battery holder or on the side of the electronic device may be provided. A user of the electronic device may then release the snapping connection by pressing this button. Such a button is preferably connected to the cover of the electronic device, but can equally be provided on the battery holder.

The electronic device can be in particular a mobile phone, but equally any other electronic device which is run with a battery.

BRIEF DESCRIPTION OF THE FIGURES

Other objects and features of the present invention will become apparent from the following detailed description considered in conjunction with the accompanying drawings, wherein

Fig. 1 to 4 illustrate steps in the assembly of a cover of an electronic device, of a battery module and of a battery holder according to an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 presents a cover 10 forming part of an electronic device, a battery 20 and a battery holder 30, which are to be assembled. The electronic device, of which only cover 10 is shown, can be for example a mobile phone.

The battery module 20 is a standard battery module which comprises electrical contacts 21 at one end.

The battery holder 30 comprises a basically even surface 31 which has a length and width slightly larger than the length and width of the battery module 20.

At the opposite side, the battery holder comprises curved guiding elements 32 which are suited to receive the battery module 20 and to hold it in place. More specifically, the guiding elements 32 are suited to receive and guide the battery module 20 when it is slid lengthwise along the battery holder 30 at the side of the battery holder opposing the surface 31 of the battery holder 30. With the guiding elements 32, the battery holder 30 has a depth which is slightly larger than the depth of the battery module 20.

On both sides of one end of the battery holder 30, i.e. at one of its narrow sides, further a small projection 33

is provided, while at the other end, a part of a snapping connection 34 is provided. Additionally, locking means (not shown) may be provided for fixing the battery module 20 to the battery holder 30. Such locking means may consist for example in a tiny projection arranged between the small projections 33, which tiny projection extends along a middle part of the corresponding narrow side of the battery holder 30 opposite to its surface 31.

The electronic device to which the presented cover 10 belongs comprises electronic components that are to be protected by the cover 10. The electronic components of the electronic device have to be powered by a battery module. To this end, the cover 10 comprises a receiving space 11, which is accessible through a cut-out in the cover 10. Length and width of the cut-out and of the receiving space 11 correspond to length and width of the battery holder 30. The depth of the receiving space 11 corresponds to the depth of the battery holder 30. In the situation presented in figure 1, the receiving space 11 is empty and open to the outside. When the cover 10 is connected to the electronic device, electrical contacts of the electronic device which are connected to the electronic components of the electronic device will be accessible via the receiving space 11 at one end of this receiving space 11, i.e. at one of its narrow sides. Further, a groove or an eye 12 is provided on both sides at the same end of the receiving space 11. At the opposite end of the receiving space 11, a part of a snapping connection 13 is provided, which is complementary to the part of the snapping connection 34 of the battery holder 30. The cover 10 of the electronic device moreover comprises a movable button 14, which

interacts with the part of the snapping connection 13 of the cover 10.

Figure 2 illustrates the first step in the assembly of the cover 10, the battery 20 and the battery holder 30. The battery module 20 was received by the guiding elements 32 of the battery holder 30 and was guided in a sliding movement lengthwise the battery holder 30 to align completely with the battery holder 30. The battery module 20 is also hold in place in this position by the guiding elements 32. As a result, basically only the electrical contacts 21 of the battery module 20 are still visible in figure 2. The battery module 20 is connected to the battery holder 30 with an orientation ensuring that the electrical contacts 21 of the battery module 20 are on the same side of the battery holder 30 as the small projections 33 of the battery holder 30.

Figure 3 now illustrates the assembly of the battery holder 30 comprising the battery module 20 with the cover 10 of the electronic device.

As can be seen in figure 3, the end of the battery holder 30 at which projection 33 is provided is inserted into the receiving space 11, namely at the end of the receiving space 11 which comprises grooves or eyes 12. The projections 33 of the battery holder 30 are thereby inserted into the corresponding grooves or eyes 12 of the cover 10 and the electrical contacts of the battery module 20 are brought into contact with the electrical contacts of the electronic device if or when the cover 10 is connected to the electronic device.

Then, the other end of the battery holder 30 is lowered, until the entire battery holder 30 is inserted completely into the receiving space 11 and until the complementary parts of the snapping connection 34, 13 of the battery holder 30 and the cover 10 interact and fix the battery holder 30 to the cover 10.

As a result, the cut-out of the cover 10 is completely filled in with the surface 31 of the battery holder 30, as can be seen in figure 4. The battery holder 30 thus forms part now of the cover 10 of the electronic device.

For removing the battery holder 30 from the cover 10 again, a user has to move button 14 slightly away from the battery holder 30, for example with a fingernail. The allowed movement of the button 14 only has to be minimal. Thereupon, the snapping connection 13, 34 is released and the user can remove the battery holder 30 from the cover 10 in order to exchange the battery module 20, if required.

With the presented embodiment of the invention, the battery module can thus be exchanged easily by a user of the electronic device. It is on the one hand easy to connect the battery module with the battery holder, and on the other hand to connect the battery holder to the electronic device.

It is to be noted that the described embodiment constitutes only one of a variety of possible embodiments of the invention.